RF2200 DATA




continuous casting machines

RF2200 HORIZONTAL CONTINUOUS CASTING MACHINE FOR COPPER ALLOYS, BRASS, BRONZE & ZINC

FEATURES OF conticast® SYSTEM:-

- PROVEN GRAPHITE CRUCIBLE TECHNOLOGY FOR LIQUID METAL CONTAINMENT – PROVIDES NATURAL DEOXIDIZING ENVIRONMENT
- TOP QUALITY GRAPHITE TOOLING FOR CONSISTANT REPEATABLE PRODUCT
- SPECIAL ALLOY HIGH THERMAL CONDUCTIVITY ultracoolers® FOR OPTIMUM HEAT TRANSFER FROM DIE TO COOLING WATER.
- LATEST GENERATION OF AC SERVOMOTORS FOR PRECISE WITHDRAWAL.
- IBM COMPATIBLE PC OPERATING ON WINDOWS XP[®]
 PROVIDING PROGRAMMABLE WITHDRAWAL
 PROFILES FOR THE AC SERVOMOTOR.



- PROVEN GRAPHITE CRUCIBLE TECHNOLOGY FOR LIQUID METAL CONTAINMENT – PROVIDES NATURAL DEOXIDIZING ENVIRONMENT
- INTRINSICALLY SAFE LOW VOLTAGE HEATERS
- THE Conticast® RF RANGE OF CONTINUOUS
 CASTING MACHINES CAN BE USED AS COMBINED
 MELTERS/CASTERS OR THEY CAN BE USED IN
 CONJUNCTION WITH A PRE-MELTING FURNACE
 (CORELESS/CHANNEL INDUCTION OR GAS/OIL FIRED
 FURNACE DEPENDING UPON THE APPLICATION)
- THE conticast® RF RANGE OF CONTINUOUS
 CASTING MACHINES ARE USED FOR THE
 MANUFACTURE OF COPPER ALLOY, BRASS, BRONZE
 AND ZINC BARS, TUBES, SECTIONS AND STRIP. THE
 RF MACHINES ARE PARTICULARLY USEFUL FOR
 PRODUCING BRASS MACHINING ROD (C36000, CZ121)
 AND BRASS FORGING ROD (C37700, CZ122)



MAXIMUM PRODUCT DIMENSIONS

- STRIP 400mm WIDE
- ROUND 250mm DIAMETER

MAXIMUM PRODUCTION RATE (depending on alloy & strand dimensions)

- COMBINED MELTING/CASTING 500kg/hour
- WITH PRE MELTER 1000kg/hour

MAXIMUM OPERATING TEMPERATURE - 1350C

CRUCIBLE CAPACITY - 2200kg (based on Copper)

CRUCIBLE SYSTEM – GRAPHITE

HEATER SYSTEM - GRAPHITE

POWER RATING - 360kW

SUPPLY VOLTAGE - 380/440V 3 PHASE 50/60Hz

HEATER VOLTAGE - 24V 3 PHASE 50/60Hz

POWER CONTROL - PHASE ANGLE/BURST FIRING SCR REGULATOR

WITHDRAWAL SYSTEM - COMPUTER CONTROLLED AC SERVOMOTOR

COMPUTER SYSTEM – WINDOWS XP PROFESSIONAL®

OPTIONAL DATA LOGGING SYSTEM -





www.conticast.com

Las

Part of HORMESA Group Las Marineras 13-17, E-28.864 Ajalvir, Madrid (ESPAÑA)

CONTICAST (R)



www.hormesa.com

Fax + 34918844382